

## MICRO-TAC AIRFREE WHITE FILM

(For indoor inside use)

(WF200)

### Details

- Having satin surface polypropylene film with unique micro-tac self-adhesive & airfree technology.
- This micro-tac glue allows an easy and 100% bubble-free application and residue-free removal on glass
- Eco-solvent, Solvent, UV ink compatibility
- Simple to stick, Simple to take away!
- Optionally, High opacity version & Anti-scratch surface available.

#### \* Condition/Setting

Highly recommend to test this sample roll before you try to target the mounthing film  
 Recommended for indoor usage only  
 Clean the mounting object before applying this film  
 Glue should not be exposed to the sunlight

### Specifications

Length (ft)	100	Width (inch)	50",54"
Weight (gsm)	280	Coating	Resin
Caliper (mil)	11.8	Base Material	Polypropylene
Inner Core (inch)	3	Printer	E S UV
Surface	Semi-matte	Adhesion at	20min 50 ≥
Min. Application	+ 40°F ( 4°C )	180° gf/25mm	24 hr 100 ≥

### KEY FEATURES

- Outstanding color expression
- Air-free liner wth micro-tac adh
- Removable & Repositionable adh.
- Wet & Dry mounts available
- No residues

### Application

- Architectural window decorations, Glass and Plastic flastness, Window graphics, Label and decals

### General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional
- Storage : Recommended to store in closed original packing in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment.  
(Humidity 35 ~ 65% RH)
- Shelf Life : One year, stored in original packing at recommended temperature  
(Coating warranty guaranteed for 6 months from date of purchase)

### How to buy :

- Please call 1-470-359-2111 to place an order or visit [www.naturamedia.us](http://www.naturamedia.us) for additional information.
- [ICC Profiles are available](#) by calling the above number.

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied.  
 All material should be tested by purchaser to determine final suitability. Printer and ink change may affact results.