

WINDOW MIRROR LIGHT FILM (WF300N)



Details

- Backlight effect by indirect light based
- Based on the frosted polyester film, it shows more vivid color expression on window.
- Reverse printing and indoor window application
- Clear hybrid removable, repositionable, re-usable adhesive, and no residue.
- For Latex & UV curable printer, Better durability

* Cautions

- Not recommended for outdoor usage
- Clean the mounting object before applying this film
- Wet mounting application
- Reverse printing is required

Specifications

Length (ft)	100	Width (inch)	54"
Weight (gsm)	200	Coating	Resin
Caliper (mil)	6.0	Base Material	PET
Inner Core (inch)	3" core	Printer	 
Surface	Matte	Adhesion at 180', gf/inch	20 ≤

KEY FEATURES

- Bright color expression by indirect light
- Installation as reverse
- No need UV white ink
- Single printing layer : Same image in&outdoor

Application

- Retail window advertisements, indoor window advertisements, Architectural window decorations

General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional
- Storage : Recommended to store in closed original packing in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment. (Humidity 35 ~ 65% RH)
- Shelf Life : One year, stored in original packing at recommended temperature (Coating warranty guaranteed for 6 months from date of purchase)

How to buy :

- Please call 1-470-359-2111 to place an order or visit www.naturamedia.us for additional information.
- **ICC Profiles are available** by calling the above number.

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.