

## FLAT DOT GLOSSY

(ZSO580)

### Details

- Digital printing PVC media that has designed to remove bubbles with high performance
- Only dry application with dot adhesive technology
- Can be repositioned initially, but the adhesive is stronger after positioned.
- Work with all popular solvent, Latex and UV curable inkjet printers.
- Dot adhesive technology, Permanent adhesive, Clear Glossy surface PVC Calender.

#### \* Adhesive strength

Initial 20 min. ≥ 700 g/inch  
Middle 1 day ≥ 900 g/inch  
Final 3 days ≥ 1,100 g/inch

#### \* Condition / Setting / Caution

- When printing, plz print out having some unprinted space
- When installing, plz have enough drying time, after printing.  
(Recommend drying times for 1 day)
- Recommending lamination to keep printed surface, because of PVC shinking matter.
- Mounted on PVC surface, it can remain residue of adhesive when removing.
- The removing of the film from heated surfaces (eg. Shop windows, steel surfaces, etc.) is not recommended. Otherwise the adhesive may completely stay on the surface. In such cases we recommend that the material and the surface is cooling down before removing.

#### \* Application surface

- Indoor & outdoor Advertising, Windows, Acrylic  
Flat or compound/curved surfaes, rivets, etc.,

#### \* Non-applicable surface

- Right-angle side, weak painted wall, embossed surface, etc.

#### \* Warranty : 6 months (1 year durability)

### Specifications

Length (ft)	164	Width (inch)	54 / 60
Weight (gsm)	-	Coating	Resin
Caliper (mil)	5.2	Base Material	PVC, Calendered
Inner Core (inch)	3	Printer	ESLUV
Surface	Clear Glossy		

### KEY FEATURES

- Dot adhesive technology
- Permanent adhesive (Initially repositionable)
- Easy to install
- Bubbles free and only dry application

### Application

- Architectural window decorations, Glass and Plastic flatness, Window graphics, Labels and decals  
Retail aisle banners

### General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional
- Storage : Recommended to store in closed original packing in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment.  
(Humidity 35 ~ 65% RH)
- Shelf Life : One year, stored in original packing at recommended temperature  
(Coating warranty guaranteed for 6 months from date of purchase)

### How to buy :

- Please call 1-470-359-2111 to place an order or visit [www.naturamedia.us](http://www.naturamedia.us) for additional information.
- [ICC Profiles are available](#) by calling the above number.

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.

[www.naturamedia.us](http://www.naturamedia.us)

1505 Pavilion Place Suite D, Norcross GA 30093

TEL 470-359-2111  
FAX 470-359-2199

**Natura**  
MAKE A DIFFERENCE