


ES680 ECO-SOL BACKLIT GLOSSY

Profiled Only

DESCRIPTION

With specialized coating layer for eco-sol ink, ECO SOL BACKLIT GLOSSY is the best choice to reproduce brilliant color with and without light for backlit signage application. High gloss surface is good enough to display express high resolution image with even diffusion of light and vivid color effects. It has advantages of water proof, fast drying time than standard backlit and sharp expression of details. It is also easy to install because of very good rigidity and flatness of 8.2 mil base polyester film.

SPECIFICATIONS

Length (m)	30	Width (inch)	36" 50" 60"
Weight (g/m ²)	290	Coating	Resin
Caliper (um)	210	Base Material	PET
Inner Core (inch)	3	Printer	
Surface	Glossy		

KEY FEATURES

- High ink limit
- Faster drying time than standard backlit
- High gloss surface
- Outstanding expression
- Even diffusion of light

APPLICATION

- Lightbox advertising, Illuminated displays, Trade show and exhibition graphics & Signage

Special Backlit application

- Cosmetics
- Fashion image
- Air Port & great image application

GENERAL INFORMATION

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional.
- Storage : Recommended to store in closed original packaging in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment.(Humidity 35~65% RH)
- Shelf Life : One year, stored in original packaging at recommended temperature.

※ Cautions

- Recommended to adjust temperature / humidity when having problem caused by static
- Recommended to test prior to use. Please be cautious about blocking issue during the take-up
- When take-up, recommended to adjust printing speed and use supplementary heating equipment
- When printing with Latex 300 Series printer, recommended to set proper pass and adjust heating temperature according to ink injection quantity (This is to prevent material's deformation by heat and low drying issue)